

# Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

## I. Chemical Product And Company Data

**PRODUCT:** ISO-FLEX HYDROSEAL

**CHEMICALFAMILY:** Cross linked-closed Cell EVA Foam  
(Plastics )

**REVISION DATE:** FEBRUARY, 2012

**MANUFACTURER:** LymTal International, Inc.

Health	0
Flammability	1
Reactivity	0
Personal Protection	A

## II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Antimony Trioxide	OSHA PEL : 0.05 mg / m3	ACGIH TLV : 0.2 mg / m3	Other Limits: N/A		
Decabromodiphenyl Ether	OSHA PEL: N/A	ACGIH TLV: N/A	Other Limits : N/A		

OTHER HAZARDS: NONE ( as supplied fully cured )

California Proposition 65 ingredients NONE

### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 ( 40CFR372)

NONE

## III. Hazards Identification

HMIS Hazard Rating No. 0

PRIMARY ROUTE OF ENTRY: Ingestion

Symptoms of Exposure

Skin Contact: No known effects.

Eyes: No known effects.

Inhalation No known effects.

Ingestion: Not expected to be a relevant route of exposure effects unknown.

Chronic No known effects

#### IV. First Aid Measures

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

#### V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: 735 \*F

Method:

General Hazard: Decomposition and combustion products may be toxic. Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Carbon dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

#### VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Not applicable

Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

#### VII. Handling And Storage

Average Shelf Life:

Refer to Product Data Sheet

#### VIII. Exposure Controls / Personal Protection

Ventilation: Standard industrial work procedures apply.

Personal Protection Equipment: Use chemical goggles/safety glasses gloves when working on a job site. Standard industrial practice should be observed at all times.

#### IX. Physical And Chemical Properties

Boiling Point (°C):	N / A	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	0 %	Solubility in Water:	0
Freezing Point (°C):	N / A	Specific Gravity (H2O=1):	0.03
Vapor Pressure @ 20° C	N / A	pH:	N/A
Vapor Density	N / A	Evaporation Rate:	N/A
Odor Threshold:	N / A	Odor:	Slight
Appearance:	Cellular PVC sheet-Foam		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

## X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability Stable under normal conditions

Incompatibility: Fire.

Hazardous Decomposition Products Oxides of Carbon; and hydrogen chloride. Combustion products may be toxic.

Conditions To Avoid Excessive heat. ( above 316 \*C ).

## XI. Toxicity Information

HMIS Hazard Rating No. 0

PRIMARY ROUTE OF ENTRY:

Ingestion. Effects Of Overexposure

Inhalation: None Known.

Eyes: None Known.

Skin Contact: None Known.

Ingestion: None Known.

Chronic: None Known.

## XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name: **NOT REGULATED**

INTERNATIONAL

DOT Proper Shipping Name NOT REGULATED

DOT Hazard Class

DOT I.D Number Label(s)

## XV. Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) NOT HAZARDOUS

CERCLA/ Super fund (40 CFR 117,302) N/A

SARA Extremely Hazardous Substances ( 40 CFR 355) N/A

SARA Hazard Categories (40 CFR 370) N/A

SARA Toxic Chemicals (40 CFR 372) See section 313 advisory in section II

Inventory Status

The chemicals in this product are listed on the US  
TSCA Chemical Substance Inventory and the  
Canadian Domestic Substances List.

#### **XVI. Other Information**

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

# Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

## I. Chemical Product And Company Data

**PRODUCT:** PRECOM ADHESIVE PART A  
**CHEMICAL FAMILY:** Epoxy resin  
**REVISION DATE:** FEBRUARY, 2012  
**MANUFACTURER:** LymTal International, Inc.  
4150 S. Lapeer Rd. Orion, MI 48359

Health	2
Flammability	1
Reactivity	0
Personal Protection	

## Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Epoxy resin: resin compound:	25068=38=6	N/E	N/E	N/E	
Non hazardous C12=C1 4 Alkylglycidyl ether	68609=97=2	N/E	N/E	N/E	

N/E = Not Established

California Proposition 65 ingredients

None

### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 ( 40CFR372)

None

## Hazards Identification

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion. Symptoms of Exposure

Skin Contact: Product may cause irritation, redness and discomfort which is transient.

Eyes: Product may cause severe irritation to the eyes.

Inhalation Vapors from product may cause irritation to the nose, throat and respiratory tract.  
Coughing and chest pains may result. High vapor concentrations may produce CNS depression.

Ingestion: Not expected to be a relevant route of exposure. Product may be slightly toxic if ingested.

#### **IV. First Aid Measures**

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

#### **V. Fire Fighting Methods**

HMIS Hazard Rating No. 1

Flash Point: (212 °F)

Method: Pensky Martin C.C.

General Hazard: None

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Water fog, carbon dioxide, or dry chemicals.

Special Fire & Unusual Hazards

Water or foam may cause violent frothing and possibly endanger the life of the firefighters, especially when sprayed into hot or burning containers.

Move containers from area if it can be done without risk. Cool fire=exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

#### **VI. Accidental Release Measures**

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste=disposal facilities.

#### **VII. Handling And Storage**

Average Shelf Life:

Refer to Product Data Sheet

Special Instructions

Store away from oxidizing agents, mineral acids, strong alkaline materials, amines and high temperatures.

#### **VIII. Exposure Controls / Personal Protection**

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person

for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

### IX. Physical And Chemical Properties

Boiling Point (°F):	425	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	0.0%	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.15
Vapor Pressure @ 25° C	0.03 mmHg	pH:	N/A
Vapor Density	> 1.0	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	slight
Appearance:	Colorless liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

### X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability Stable

Incompatibility: Strong acids, oxidizing agents, bases, amines and mercaptans.

Hazardous Decomposition Products Oxides of Carbon; aldehydes and acids. Decomposition and combustion products may be toxic.

Conditions To Avoid Strong acids in bulk. Hardeners for epoxy resins unless done by experienced individuals.

### XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, and eyes. Effects Of Overexposure

Inhalation: May cause irritation to the respiratory tract.

Eyes: May be severely irritating to the eyes.

Skin Contact: Irritating to the skin. In some individuals it may cause sensitization.

Ingestion: May cause permanent damage to the mouth throat and stomach.

Chronic: This product does not contain chemicals considered to be carcinogenic by OSHA Hazardous Communications Act 1910.1200.

### XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

### XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## **XIV. Transport Information**

DOT SHIPPING INFORMATION:

**NOT REGULATED**

## **XV. Regulatory Information**

OSHA Hazard Communication Standard (29 CFR 1910.1200)	Hazardous
CERCLA/ Super fund (40 CFR 117,302)	N/A
SARA Extremely Hazardous Substances ( 40 CFR 355)	N/A
SARA Hazard Categories (40 CFR 370)	Health: Immediate Physical: None
SARA Toxic Chemicals (40 CFR 372) Inventory Status	None The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

## **XIV. Other Information**

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

# Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

## I. Chemical Product And Company Data

**PRODUCT:** PRECOM ADHESIVE PART B  
**CHEMICALFAMILY:** Amine Mixture  
**REVISION DATE:** FEBRUARY, 2012  
**MANUFACTURER:** LymTal International, Inc.  
4150 S. Lapeer Rd. Orion, MI 48359

Health	2
Flammability	1
Reactivity	0
Personal Protection	

## Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Tetra Ethylene Pentamine	112-57-2	N/E	N/E	N/E	< 5 %
Tall Oil Fatty Acid	68953-36-6	N/E	N/E	N/E	
Nonyl Phenol	25154-52-3	N/E	N/E	N/E	
N-Aminoethylpiperazine	140-31-8	N/E	N/E	N/E	
Polyoxyalkyleneamine	9046-10-0	N/E	N/E	N/E	
Diethylene Tetramine	111-40-0	N/E	N/E	N/E	

N/E = Not Established

California Proposition 65 ingredients

None

### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

None

## Hazards Identification

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion. Symptoms of Exposure

Skin Contact: Corrosive to the skin. May cause skin sensitization.

Eyes: Product may cause severe irritation to the eyes and may cause severe damage including blindness.

Inhalation: Vapors or mist may be corrosive to the upper respiratory tract. Long term exposure may result in lung damage which will be apparent by shortness of breath and a chronic cough.

Ingestion: Not expected to be a relevant route of exposure. It may however cause permanent damage to the throat mouth and stomach.

#### **IV. First Aid Measures**

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

#### **V. Fire Fighting Methods**

HMS Hazard Rating No. 1

Flash Point: (240 °F)

Method: Pensky Martin C.C.

General Hazard: None

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: 1.0%

UEL: Not available

Extinguishing Media

For small fires, use foam, CO<sub>2</sub>, or dry chemical. For large fires, use water spray, or fog.

Special Fire & Unusual Hazards Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

#### **VI. Accidental Release Measures**

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

#### **VII. Handling And Storage**

Average Shelf Life:

Refer to Product Data Sheet

Special Instructions

Store away from open flames and high temperatures > 150 °F

#### **VIII. Exposure Controls / Personal Protection**

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference

OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

## IX. Physical And Chemical Properties

Boiling Point (°F):	259	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	0.1% (0.97g/l)	Solubility in Water:	slight
Freezing Point (°C):	N/A	Specific Gravity @20° C	0.97
Vapor Pressure @ 25° C	0.05 mmHg	pH:	N/A
Vapor Density	7.6	Evaporation Rate:	0.007
Odor Threshold:	N/A	Odor:	Ammonical
Appearance:	Amber liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

## X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability Stable

Incompatibility: Strong acids, oxidizing agents, bases, amines and mercaptans.

Hazardous Decomposition Products Carbon dioxide and oxides of nitrogen. Decomposition and combustion products may be toxic.

Conditions To Avoid Avoid heat, flame and contact with strong oxidizing agents.

## XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, and eyes. Effects Of Overexposure

Inhalation: Vapors may be corrosive to the upper respiratory tract.

Eyes: May cause severe damage including blindness.

Skin Contact: Irritating to the skin. In some individuals it may cause sensitization.

Ingestion: May cause permanent damage to the mouth throat and stomach.

Chronic: This product does not contain chemicals considered to be carcinogenic by OSHA Hazardous Communications Act 1910.1200.

## XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## **XIV. Transport Information**

### DOT SHIPPING INFORMATION

**DOT Proper Shipping Name Corrosive liquid, N.O.S (Nonyl Phenol)**

**DOT Hazard Class 8, PGIII**

**DOT I.D. Number UN1760**

**DOT PLACARD**

## **XV. Regulatory Information**

OSHA Hazard Communication Standard  
(29 CFR 1910.1200)

Hazardous

CERCLA/ Super fund (40 CFR 117,302)

N/A

SARA Extremely Hazardous Substances  
(40 CFR 355)

N/A

SARA Hazard Categories (40 CFR 370)

Health: Immediate  
Delayed  
Physical: None

SARA Toxic Chemicals (40 CFR 372)  
Inventory Status

None  
The chemicals in this product are listed on the US  
TSCA Chemical Substance Inventory and  
the Canadian Domestic Substances List.

## **XIV. Other Information**

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.