

Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

I. Chemical Product And Company Data

PRODUCT: ISO-FLEX 750 BASECOAT, PART A
CHEMICALFAMILY: Polyurethane prepolymer (TDI base)
REVISION DATE: JAN 2010
DOCUMENT ID : 750 B.C.- PT.A, VERSION 1.0
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 1 |
| Reactivity | 1 |
| Personal Protection | H |

II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

| HAZARDOUS INGREDIENTS | CAS NO | EXPOSURE LIMITS | | | CONTENT |
|-------------------------|------------|-----------------|------|--------|---------|
| | | TLV | STEL | PEL | |
| Magnesium Silicate | 14807-96-6 | N/A | N/A | N/A | <13.0% |
| Petroleum Hydrocarbons | 64742-95-6 | 100ppm | N/A | 100ppm | 4.67% |
| Proprietary Ingredients | | | | | Balance |

California Proposition 65 ingredients

| | | |
|----------------------|------------|-------|
| Toluene Diisocyanate | 26471-62-5 | <1.0% |
|----------------------|------------|-------|

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

| | | | | | |
|------------------------|------------|----------|---------|----------|--------|
| 1,2,4-Trimethylbenzene | 95-63-6 | 25ppm | N/A | 25ppm | 2.37% |
| Ethyl Benzene | 100-41-4 | 100ppm | 125ppm | 100ppm | 0.037% |
| Xylene | 1330-20-7 | 100ppm | 150ppm | 100ppm | 2.37% |
| Cumene | 98-82-8 | 50ppm | N/A | 50ppm | 0.11% |
| Toluene Diisocyanate | 26471-62-5 | 0.005ppm | 0.02ppm | 0.005ppm | <1.0% |

III. Hazards Identification

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

Skin Contact: Contact can cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching and hives.

Eyes: Product may cause severe irritation, redness and tearing to the eyes.

Inhalation Vapors can be irritating to nose and mucous membranes. High exposures may result in tightness or burning in the chest, coughing, headaches, and fatigue. Respiratory sensitivity may result in asthma like symptoms and on subsequent exposure even below the TLV.

Ingestion: Not expected to be a relevant route of exposure although it may cause permanent damage to the mouth throat and stomach, gastrointestinal irritation, nausea vomiting diarrhea and headache.

IV. First Aid Measures

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance

Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.

Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: > 99°C (>210 °F)

Method: Tag C.C.

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Use foam, Carbon dioxide, or dry chemical.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved; pressure demand self-contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Average Shelf Life:

Refer to Product Data Sheet

Special Instructions

Store in a cool dry place.

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves

and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

| | | | |
|------------------------|------------------------------------|-------------------------------------|----------------------------------|
| Boiling Point (°C): | N/D | Water/Oil Distribution Coefficient: | N/A |
| VOC Content g/l: | Part A 120 g/l A+B Mixed 99 g/l | Specific Gravity @20° C | A only: 1.139 A+B Mixed: 1.12 |
| Freezing Point (°C): | N/A | Solubility in Water: | Negligible |
| Vapor Pressure @ 20° C | <0.01 | pH: | N/A |
| Vapor Density | >air | Evaporation Rate: | N/A |
| Odor Threshold: | N/A | Odor: | Slight |
| Appearance: | Gray liquid | | |
| N/A = Not Available | N/D=NOT Determined | Ca. = Approximate | |

X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable

Incompatibility:

Strong acids, oxidizing agents reducing agents, bases, peroxides amines and water.

Hazardous Decomposition Products

Oxides of Carbon; nitrogen; TDI, and hydrogen cyanide. Decomposition and Combustion products may be toxic.

Conditions To Avoid

Water as well as chemicals mentioned in incompatibility.

XI. Toxicity Information

HMIS Hazard Rating No. 2

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes and ingestion.

Effects Of Overexposure

Inhalation:

Vapors may be irritating to the upper respiratory tract.

Eyes:

Contact can cause severe irritation.

Skin Contact:

Irritating to the skin. In some individuals it may cause sensitization.

Ingestion:

May cause permanent damage to the mouth throat and stomach.

Chronic:

This product does contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, and OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

DOT Proper Shipping Name NOT REGULATED

DOT Hazard Class

DOT I.D Number

Label(s)

XV. Regulatory Information

OSHA Hazard Communication Standard
(29 CFR 1910.1200)

Hazardous

CERCLA/ Super fund (40 CFR 117,302)

N/A

SARA Extremely Hazardous Substances
(40 CFR 355)

N/A

SARA Hazard Categories (40 CFR 370)

Health : Immediate

Physical: Fire

SARA Toxic Chemicals (40 CFR 372)
Inventory Status

None

The chemicals in this product are listed on the US
TSCA Chemical Substance Inventory and the
Canadian Domestic Substances List.

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.

Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

I. Chemical Product And Company Data

PRODUCT: ISO-FLEX 750 BASECOAT, PART B
CHEMICALFAMILY: Polyamine Solution
REVISION DATE: JAN 2010
DOCUMENT ID : 750 B.C.- PT.B, VERSION 1.0
MANUFACTURER: LymTal International, Inc.
4150 S. Lapeer Rd. Orion, MI 48359

| | |
|---------------------|---|
| Health | 1 |
| Flammability | 1 |
| Reactivity | 0 |
| Personal Protection | H |

II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

| HAZARDOUS INGREDIENTS | CAS NO | EXPOSURE LIMITS | | | CONTENT |
|---|------------|-----------------|------|--------|-------------------|
| | | TLV | STEL | PEL | |
| N,N'-dialkylaminodiphenyl -methane | 5285-60-9 | None | None | None | <95% |
| Petroleum Hydrocarbons Proprietary Ingredients | 64742-95-6 | 100ppm | N/A | 100ppm | 10.05% Balance |

California Proposition 65 ingredients

None

Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

| | | | | | |
|------------------------|-----------|-----------|--------|--------|-------|
| MDA | 101-77-9 | <0.05 wt% | | | |
| 1,2,4-Trimethylbenzene | 95-63-6 | 25ppm | N/A | 25ppm | 5.10% |
| Ethyl Benzene | 100-41-4 | 100ppm | 125ppm | 100ppm | 0.08% |
| Xylene | 1330-20-7 | 100ppm | 150ppm | 100ppm | 0.48% |
| Cumene | 98-82-8 | 50ppm | N/A | 50ppm | 0.24% |

III. Hazards Identification

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

Skin Contact: Prolonged or repeated exposure may cause mild irritation and sensitization may occur.
Eyes: Contact can cause mild irritation.

Inhalation At room temperature, exposures to vapors are unlikely due to physical properties; higher temperatures may generate vapor levels sufficient to cause irritation and other effects.
Ingestion: Not expected to be a relevant route of exposure although it is expected to be toxic through ingestion.

IV. First Aid Measures

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance
Eyes Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.
Skin Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
Ingestion Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

V. Fire Fighting Methods

HMIS Hazard Rating No. 1

Flash Point: 149 °C (300°F)

Method: Pensky Martin C.C

General Hazard: Decomposition and combustion products may be toxic.

Auto-Ignition Temp.: Not Available

Limits of Flammability

LEL: Not Available

UEL: Not Available

Extinguishing Media

Carbon Dioxide, foam, dry chemical and water fog.

Special Fire & Unusual Hazards

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved; pressure demand self-contained breathing apparatus and full protective gear.

VI. Accidental Release Measures

Action To Take For Spills/ Leaks: Avoid contact with skin or eyes. Ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material.

Waste Disposal Method: Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

VII. Handling And Storage

Average Shelf Life:

Refer to Product Data Sheet

Special Instructions

Store in cool, dry place.

VIII. Exposure Controls / Personal Protection

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard.

Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

IX. Physical And Chemical Properties

| | | | |
|------------------------|------------------------------------|-------------------------------------|----------------------------------|
| Boiling Point (°C): | 441 | Water/Oil Distribution Coefficient: | N/A |
| VOC Content g/l: | Part B 195 g/l A+B Mixed 99 g/l | Specific Gravity @20° C | B only: 0.983 A+B Mixed: 1.12 |
| Freezing Point (°C): | N/A | Solubility in Water: | Negligible |
| Vapor Pressure @ 20° C | <1 | pH: | N/A |
| Vapor Density | 10.7 | Evaporation Rate: | N/A |
| Odor Threshold: | N/A | Odor: | Ammonical |
| Appearance: | Brown liquid | | |
| N/A = Not Available | N/D=NOT Determined | Ca. = Approximate | |

X. Stability And Reactivity

HMIS Hazard Rating No. 0

Stability

Stable

Incompatibility:

Peroxides, oxidizing and reducing agents and sources of ignition

Hazardous Decomposition Products

Oxides of Carbon; and nitrogen; Decomposition and Combustion products may be toxic.

Conditions To Avoid

See incompatibility.

XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes, ingestion.

Effects Of Overexposure

Inhalation:

Unlikely at room temperatures at elevated temperatures may cause irritation.

Eyes:

Contact can cause mild irritation

Skin Contact:

In some individuals it may cause sensitization.

Ingestion:

May cause permanent damage to the mouth throat and stomach.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, and OSHA.

XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

XIV. Transport Information

DOT SHIPPING INFORMATION

Not regulated

XV. Regulatory Information

| | |
|---|---|
| OSHA Hazard Communication Standard (29 CFR 1910.1200) | Hazardous |
| CERCLA/ Super fund (40 CFR 117,302) | N/A |
| SARA Extremely Hazardous Substances (40 CFR 355) | N/A |
| SARA Hazard Categories (40 CFR 370) | Health : Immediate Physical: None |
| SARA Toxic Chemicals (40 CFR 372) Inventory Status | None The chemicals in this product are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List. |

XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPLIED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.