

# Material Safety Data Sheet

Emergency Phone:(248)-373-8100 24-Hour CHEMTREC (800)-424-9300 CHEMTREC, D.C. Area (800)-483-7616

## I. Chemical Product And Company Data

**PRODUCT:** ISO-FLEX LUBE ADHESIVE  
**CHEMICALFAMILY:** Polyurethane  
**REVISION DATE:** MARCH 2007  
**MANUFACTURER:** LymTal International, Inc.  
4150 S. Lapeer Rd. Orion, MI 48359

Health	1
Flammability	1
Reactivity	1
Personal Protection	X

## II. Composition / Information On Ingredients

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be made available as provided in this standard. All components of this product are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

HAZARDOUS INGREDIENTS	CAS NO	EXPOSURE LIMITS			CONTENT
		TLV	STEL	PEL	
Calcium Carbonate	1317-65-3	N/A	N/A	N/A	< 15.0%
Diphenylmethanediisocyanate	26447-40-5	N/A	N/A	N/A	< 1.5%
Modified MDI	Not Disclosed	N/A	N/A	N/A	3.75%
Petroleum Hydrocarbons	64742-95-6	100 ppm	N/A	N/A	3.15%
Proprietary Ingredients					Balance

### California Proposition 65 ingredients

None

### Section 313 Supplier Notification

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40CFR372)

1,2,4-Trimethylbenzene	95-63-6	25 ppm	N/A	25 ppm	1.6%
Ethyl Benzene	100-41-4	100 ppm	125 ppm	100 ppm	0.025%
Xylene	1330-20-7	100ppm	150ppm	100ppm	0.15%
Cumene	98-82-8	50 ppm	N/A	50 ppm	0.075%

## III. Hazards Identification

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Eye and skin contact, breathing and ingestion.

Symptoms of Exposure

**Skin Contact:** Contact may cause moderate skin irritation. In some individuals exposure may result in allergic type symptoms causing rash, itching and hives.

**Eyes:** Contact can cause severe irritation, redness, tearing and blurred vision.  
**Inhalation** Vapors can be irritating to nose and mucous membranes. Exposures may result in tightness or burning in chest, coughing, headache and fatigue. Respiratory sensitivity may result in asthma like symptoms and on subsequent exposure even below the TLV.  
**Ingestion:** Not expected to be a relevant route of exposure although it can cause gastrointestinal irritation, nausea, vomiting diarrhea and headache.

#### IV. First Aid Measures

**Inhalation** Remove victim from exposure. If difficulty with breathing, administer oxygen and seek medical assistance  
**Eyes** Flush eyes with cold water for a minimum of 15 minutes, lifting lower and upper eye lids throughout. Seek immediate medical attention.  
**Skin** Immediately remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.  
**Ingestion** Do not induce vomiting, get immediate medical attention, if vomiting occurs spontaneously keep head below hips to prevent aspiration of liquids into lungs. Do not give anything by mouth to an unconscious person

#### V. Fire Fighting Methods

HMIS Hazard Rating No. 1

**Flash Point:** (>60 °C > 105 °F )

**Method:** Pensky Marten .

**General Hazard:** Decomposition and combustion products may be toxic.

**Auto-Ignition Temp.:** Not Available

**Limits of Flammability**

LEL: Not Available

UEL: Not Available

**Extinguishing Media**

Carbon dioxide, foam, dry chemical and water fog.

**Special Fire & Unusual Hazards**

Move containers from area if it can be done without risk. Cool fire-exposed containers with water from the side. As in any fire, wear NIOSH/MSHA approved, pressure demand self contained breathing apparatus and full protective gear.

#### VI. Accidental Release Measures

**Action To Take For Spills/ Leaks:** Avoid contact with skin or eyes. ventilate area, and eliminate all sources of ignition. Wear appropriate protective gear, contain leak or spill, salvage, clean up residue with absorbent material. This product is heavier than and insoluble in water. Wash down area using a soap solution and allow 10 minutes to react.

**Waste Disposal Method:** Handle disposal of waste material in a manner that complies with local, state, province and federal regulation. Landfill if solidified, or incineration at agency approved waste-disposal facilities.

#### VII. Handling And Storage

Average Shelf Life:

Refer to Product Data Sheet

Special Instructions

Store in a cool dry place.

#### VIII. Exposure Controls / Personal Protection

**Ventilation:** Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of heavy vapors.

**Personal Protection Equipment:** Do NOT wear contact lenses when working with this material. Use chemical goggles/safety glasses with side shields and impervious gloves. Wear clothing with long sleeves and pants. In operations where mists can be generated or the exposure limits for crystalline silica

exceeded, wear a NIOSH/MSHA approved dust/fume respirator selected by a technically qualified person for the specific work conditions. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH approved respirators for listed hazard. Confined spaces, room, or tanks are areas where concern for TLV's is especially important. Reference OSHA regulation CFR 29 1910.134 for recommended respiratory protection.

## IX. Physical And Chemical Properties

Boiling Point (°C):	N/A	Water/Oil Distribution Coefficient:	N/A
Percent Volatile:	Ca 5% ( 55 g/l )	Solubility in Water:	Negligible
Freezing Point (°C):	N/A	Specific Gravity @20° C	1.08
Vapor Pressure @ 20° C	N/A	pH:	N/A
Vapor Density	< 0.01	Evaporation Rate:	N/A
Odor Threshold:	N/A	Odor:	Aromatic
Appearance:	Pigmented liquid		
N/A = Not Available	N/D=NOT Determined	Ca. = Approximate	

## X. Stability And Reactivity

HMIS Hazard Rating No. 1

Stability

Stable, avoid contact with moisture.

Incompatibility:

Strong oxidizing agents and reducing agents, strong acids, bases, amines and peroxides..

Hazardous Decomposition Products

Oxides of Carbon; and nitrogen; Decomposition and Combustion products may be toxic.

Conditions To Avoid

Strong acids, bases, amines and peroxides in bulk.

## XI. Toxicity Information

HMIS Hazard Rating No. 1

PRIMARY ROUTE OF ENTRY: Inhalation, dermal, eyes and ingestion.

Effects Of Overexposure

Inhalation:

Vapors can be irritating to nose and mucous membranes.

Eyes:

Contact can cause severe irritation.

Skin Contact:

In some individuals it may cause sensitization.

Ingestion:

May cause permanent damage to the mouth throat and stomach.

Chronic:

This product does not contain chemicals considered to be carcinogenic by NTP, IRAC, ACGIH, OSHA.

## XII. Ecological Information

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## XIII. Disposal Considerations

Handle disposal of waste material in a manner that complies with all applicable local, state, provincial and federal regulations.

## XIV. Transport Information

### DOT SHIPPING INFORMATION

DOT Proper Shipping Name NOT REGULATED

DOT Hazard Class

DOT I.D Number

Label(s)

## XV. Regulatory Information

OSHA Hazard Communication Standard  
(29 CFR 1910.1200)

Hazardous

CERCLA/ Super fund (40 CFR 117,302)

N/A

SARA Extremely Hazardous Substances  
(40 CFR 355)

N/A

SARA Hazard Categories (40 CFR 370)

Health : Immediate

Physical: Delayed

SARA Toxic Chemicals (40 CFR 372)  
Inventory Status

See section 313 advisory in section II

The chemicals in this product are listed on the US  
TSCA Chemical Substance Inventory and the  
Canadian Domestic Substances List.

## XVI. Other Information

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, LymTal INTERNATIONAL INC. CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE ANY WARRANTIES, NOR ASSUMES ANY LIABILITY, FOR ITS USE.